


Infiniṭē™ 6A

Category 6A UTP Patch Cord

Features:

- High-performance data communications Cat 6A UTP patch cord
- Comply with Cat 6A standards: ANSI/TIA/EIA 568C and ISO/IEC 11801:2002 Class EA
- Unshielded 4-pair stranded cable
- Suitable for EIA 568A/B applications
- Available in different length
- LSZH sheath complies with IEC 60332-1 & 3C, IEC 60754-1 & 2, IEC 61034-2 and ASTM D-2863



Performance:

Frequency	RL	Attenuation	NEXT	PSNEXT	ANEXT	PSANEXT
	dB	dB/100m	dB	dB	dB	dB
1 MHz	23	2	80.3	78.3	79	67
4 MHz	26	3.7	71.3	69.3	79	67
10 MHz	28	5.8	65.3	63.3	79	67
100 MHz	23.1	18.8	50.3	48.3	78	63.1
200 MHz	21	27.2	45.8	43.8	73.5	61.5
300 MHz	19.8	33.8	43.1	41.1	70.8	58.8
400 MHz	18.9	39.6	41.3	39.3	69	57
500 MHz	18.2	44.8	39.8	37.8	67.5	55.5
660 MHz	17.4	52.3	38.0	36.0	65.7	53.7

Ordering Information:

Order no.	Description
IN6A-3**-XX	Cat 6A UTP Patch Cord
** = Length in meter	
XX= Color Code (GR = Grey, RD = Red, YL = Yellow, BL = Blue, etc.)	



* Infiniṭē Cable System reserves the right to modify products and specifications without prior notice.