


Infini^{tilde} 5e

Category 5e UTP Patch Cord

Features:

- High-performance data communications Cat 5e UTP patch cord
- Comply with Cat 5e standards: ANSI/TIA/EIA 568 and ISO/IEC 11801:2002 Class D 2nd Edition
- Unshielded 4-pair stranded cable
- Slim boot design is suitable for high density active equipment
- Suitable for EIA 568A/B applications
- Available in different length
- LSZH sheath complies with IEC 60332-1 & 3C, IEC 60754-1 & 2, IEC 61034-2, ASTM D-2863 and BS EN ISO 4589-3.




Performance:

| Frequency | RL dB | Attenuation dB/100m | NEXT dB | PSNEXT dB | ELFEXT dB | PSELFEXT dB |
|-----------|----------|------------------------|------------|--------------|--------------|----------------|
| 1 MHz | 20.0 | 2.5 | 65.3 | 62.3 | 63.8 | 60.8 |
| 4 MHz | 23.0 | 4.9 | 56.3 | 53.3 | 51.7 | 48.7 |
| 10 MHz | 25.0 | 7.8 | 50.3 | 47.3 | 43.8 | 40.8 |
| 16 MHz | 25.0 | 9.9 | 47.3 | 44.2 | 39.7 | 36.7 |
| 20 MHz | 25.0 | 11.1 | 45.8 | 42.8 | 37.8 | 34.8 |
| 31.25 MHz | 23.6 | 14.1 | 42.9 | 39.9 | 33.9 | 30.9 |
| 62.5 MHz | 21.5 | 20.4 | 38.4 | 35.4 | 27.8 | 24.9 |
| 100 MHz | 20.1 | 26.4 | 35.3 | 32.3 | 23.8 | 20.8 |

Ordering Information:

| Order no. | Description |
|--|----------------------------|
| IN5E-3**-XX | Cat 5e UTP PVC Patch Cord |
| IN5E-3**-XX-S | Cat 5e UTP LSZH Patch Cord |
| ** = Length in meter (01=1m, 02=2m, 03=3m, etc.) | |
| XX= Color Code (GR = Grey, RD = Red, YL = Yellow, BL = Blue, etc.) | |



*These figures are nominal values.
*Infinite Cable System reserves the right to modify products and specifications without prior notice.

