


# Infiniċ™ 6

## Category 6 UTP Patch Cord

### Features:

- High-performance data communications Cat 6 UTP patch cord
- Comply with Cat 6 standards: ANSI/TIA/EIA 568C and ISO/IEC 11801:2002 Class E 2<sup>nd</sup> Edition
- Unshielded 4-pair stranded cable
- Slim boot design is suitable for high density active equipment
- Suitable for EIA 568A/B applications
- Available in different length
- LSZH sheath complies with IEC 60332-1 & 3C, IEC 60754-1 & 2, IEC 61034-2 and ASTM D-2863



### Performance:

Frequency	RL dB	Attenuation dB/100m	NEXT dB	PSNEXT dB	ELFEXT dB	PSELFEXT dB
1 MHz	20.0	2.0	74.3	72.3	67.8	64.8
10 MHz	25.0	6.0	59.3	57.3	47.8	44.8
16 MHz	25.0	7.6	56.2	54.3	43.7	40.7
20 MHz	25.0	8.5	54.8	52.8	41.8	38.8
62.5 MHz	21.5	15.4	47.4	45.4	31.9	28.9
100 MHz	20.1	19.8	44.3	42.3	27.8	24.8
200 MHz	18.0	29.0	39.8	37.8	21.8	18.8
250 MHz	17.3	32.8	38.3	36.3	19.8	16.8

### Ordering Information:

Order no.	Description
IN6-3**-XX	Cat 6 UTP Patch Cord
** = Length in meter	
XX= Color Code (GR = Grey, RD = Red, YL = Yellow, BL = Blue, etc.)	



\* Infiniċ Cable System reserves the right to modify products and specifications without prior notice.